

<tab-folder> and <tab-item>

Creates TabFolder and TabItem.

Example : TabFolder with 5 tabs.

<tab-folder>

```
<composite id="ctab1">
  <fill-layout />
  <group text="group test"
    style="SWT.SHADOW_ETCHED_OUT">
    <grid-layout numcolumns="2" equalwidth="true" />
    <label text="Combo test" />
    <combo style="SWT.READ_ONLY">
      <item>abc1</item>
      <item>abc2</item>
      <select>1</select>
    </combo>
    <label text="List test" />
    <list style="SWT.BORDER">
      <menu>
        <menu-item text="click me"
          style="SWT.PUSH" />
        <menu-item text="sub-menuitem"
          style="SWT.CASCADE">
          <menu>
            <menu-item text="sub-menuitem-1"
              style="SWT.PUSH" />
          </menu>
        </menu-item>
        <menu>
          <menu-item text="sub-menuitem-2"
            style="SWT.PUSH" />
        </menu>
      </menu>
      <item>list1</item>
      <item>list2</item>
      <item>list3</item>
      <select>1</select>
    </list>
  </group>
</composite>
<tab-item text="tab1" _control="ctab1" />

<composite id="ctab2">
  <fill-layout />
  <table
    style="SWT.VIRTUAL | SWT.BORDER | SWT.V_SCROLL"
    linesVisible="true" headerVisible="true" itemCount="1000"
    SWT.SetData="com.sheelapps.swtмл.examples.TestListener">
    <table-column text="column1" style="SWT.LEFT">
```

```

        width="150" />
        <table-column text="column2" width="100" />
    </table>
</composite>
<tab-item text="tab2" _control="ctab2" />

    <composite id="ctab3">
        <fill-layout />
        <tree
            style="SWT.VIRTUAL | SWT.BORDER | SWT.V_SCROLL"
            linesVisible="true" headerVisible="true" itemCount="20"
            SWT.SetData="com.sheelapps.swtml.examples.TestListener">
            <tree-column text="column1" style="SWT.LEFT"
                width="150" />
            <tree-column text="column2" width="100" />
        </tree>
    </composite>
<tab-item text="tab3" style="SWT.V_SCROLL" _control="ctab3" />

    <composite id="ctab4">
        <fill-layout />
        <sash-form style="SWT.HORIZONTAL">
            <row-layout />
            <styled-text text="Styled Text"
                style="SWT.BORDER" />
            <text text="Text" style="SWT.BORDER"
                SWT.Modify="com.sheelapps.swtml.examples.TestListener">
                <menu>
                    <menu-item text="show text" />
                    <menu-item style="SWT.SEPARATOR" />
                    <menu-item text="second menu " />
                </menu>
            </text>
        </sash-form>
    </composite>
<tab-item text="tab4" _control="ctab4" />

    <composite id="ctab5">
        <row-layout />
        <button text="Ok"
            SWT.Selection="com.sheelapps.swtml.examples.TestListener" />

        <button text="Cancel" />
    </composite>
<tab-item text="tab5" _control="ctab5" />

</tab-folder>

```

tab1

tab2

tab3

tab4

tab5

group test

Combo test

abc2

▼

List test

list1

list2

list3